



## SAFETY DATA SHEET

Well•Worth Products, Inc. 180 Dutton Avenue Buffalo, NY 14211 USA

# PRODUCT: Well•Worth Crystal Clear Glass Cleaner - 20 oz.

### CODE: 1001

#### Section 01: Chemical product and company identification

Product Item Numbers Product Identity Manufactured for	1001 Well•Worth Crystal Clear Glass Cleaner - 20 OZ. Well•Worth Products, Inc. 180 Dutton Ave. Buffalo, NY USA 14211 wellworthproducts.com Tel: 800-890-7935 Fax: 716-597-0217
24 hour emergency telephone number Recommended Use Consumer Commodity	

## Section 02: HAZARDS IDENTIFICATION

А

Signal Word	DANGER.
Signal Word Hazard Classification	
Hazard Description	H225 Highly flammable liquid and vapour. H222 Extremely flammable aerosol . H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H319
Precautionary Statements	Causes serious eye irritation. H336 May cause drowsiness or dizziness. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P233 Keep container tightly closed. P240 Croupd and bend continer and receiving activity mont. P211 Lise explosion proof.
	P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P251 Do not pierce or burn container, even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.
Response	P302 + P352 - If on skin: wash with plenty of water P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P312 Call a poison center/doctor if you feel unwell. P321 - Consult with a doctor or poison control centre if skin is itchy or a skin rash develops or you feel unwell. P332 + P313 - If skin irritation occurs get medical attention or advice. P337 + P313 - If eye
	irritation persists get medical attention. P362 + P364 - Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or 6% foam.
Storage	P403 Store in a well ventilated area. P403 + P233 Store in a well ventilated area. Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50C / 122F.
Disposal	P501 Dispose all unused, waste or empty containers in accordance with local regulations.

А

### Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
ISOPROPYL ALCOHOL	67-63-0	
ISOBUTANE	75-28-5	
BUTYL CELLOSOLVE	111-76-2	
AMMONIA	7664-41-7	

# PRODUCT: PF 513 GLASS CLEANER

#### Section 04: First aid measures

Eye contact	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
	least 15 minutes. Obtain medical attention.
Skin contact	Remove all contaminated clothing and immediately wash the exposed areas with copious
	amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation	
	difficult, give oxygen, obtain medical attention.
Ingestion	
5	immediately. If spontaneous vomiting occurs have victim lean forward with head down to
	prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious
	person.
Additional information	
	into the lungs. In the event of an incident involving this product ensure that medical
	authorities are provided a copy of this safety data sheet.

#### Section 05: Fire fighting measures

Extinguishing media Hazardous combustion products Special fire fighting procedures	"Alcohol" foam, CO2, dry chemical. In cases of larger fires, water spray should be used. Oxides of carbon (CO, CO2). Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Heat will cause pressure buildup and may cause explosive rupture.
Section 0	06: Accidental release measures

Leak/spill...... Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).

#### Section 07: Handling and storage

Handling procedures	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from
Storage needs	heat, sparks, and open flame. Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

#### Section 08: Exposure controls / personal protection

Protective equipment	Liquid chemical goggles.	
Eye/type	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator	
Respiratory/type	when contaminant levels exceed the recommended exposure limits.	
Gloves/ type Clothing/type Footwear/type Other/type Ventilation requirements Exposure limits	Chemical resistant gloves. Wear adequate protective clothes. Safety boots per local regulations. Emergency showers and eye wash stations should be available.	

Ingredients	ACGI	H TLV	OSH/	A PEL	NIOSH
	TWA	STEL	PEL	STEL	REL
ISOPROPYL ALCOHOL	200 ppm	400 ppm	400 ppm	500 ppm	400 ppm
ISOBUTANE	Not established 20 ppm	Not established	Not established	Not established	800 ppm
BUTYL CELLOSOLVE		No data	50 ppm	25 ppm (vacated)	5 ppm
AMMONIA	25 ppm	35 ppm 15 minutes	50 ppm	35 ppm (vacated)	35 ppm - 35 ppm STEL 15 minutes

# **PRODUCT: PF 513 GLASS CLEANER**

# Section 09: Physical and chemical properties

Freezing point (deg C) No data.   Solubility Complete.   Boiling point (deg C) -12°C.   Evaporation rate Slower than n-butyl acetate.   Flash point (deg C), method 12.0 °C Closed Cup117°C Closed Cup (proppellant).   Auto ignition temperature (deg C) 8.4.   Lower flammable limit (% vol) 8.4.   Coefficient of water\oil distribution No data.   % Volatile by volume	Solubility Boiling point (deg C) Evaporation rate Flash point (deg C), method Auto ignition temperature (deg C) Upper flammable limit (% vol) Lower flammable limit (% vol) Coefficient of water\oil distribution % Volatile by volume VOC	Clear, colourless. Ammonia. No data. 25-35 psig @ 70f. >1. Not applicable. Liquid: 0.97 lb/usg (0.12 g/mL) Aerosol: 0.946 lb/usg (0.11 g/mL). No data. Complete. -12°C. Slower than n-butyl acetate. 12.0 °C Closed Cup117°C Closed Cup (proppellant). 460 °C (propellant) . 8.4. 1.8. No data. 22. 1.32 lb/usg - 159 g/L.
---	---	---

# Section 10: Stability and reactivity

Stability	Stable at normal temperatures and pressures.
Reactivity conditions	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong
	oxidizing agents.
Incompatibility	Keep away from heat. Incompatible with strong oxidizers.
Hazardous products of decomposition	By fire:. Dense black smoke. Oxides of carbon (CO,CO2).
Hazardous polymerization	Hazardous polymerization will not occur.

# Section 11: Toxicological information

Route of entry Effects of chronic exposure		effects. Prolonged or repeated skir Intentional misuse by deliberately of	on. apour may cause anesthetic effects and serious health n contact may cause drying or cracking of skin. concentrating and inhaling this product may be harmful
Skin contact Skin absorption Eye contact Inhalation (acute) Inhalation (chronic)		vomiting and unconsciousness. Chronic exposure to organic solver effects including permanent brain a	h the skin. le destruction. an cause respiratory irritation, dizziness, headache, nt vapors have been associated with various neurotoxic and/or nervous system damage, kidney, liver, blood
damage and reproductive effects among women. Symptoms may include na vomiting, abdominal pain, headache, impaired memory, loss of coordination breathing difficulties.   Ingestion May be harmful or fatal if swallowed. Swallowing causes inebriation, headache leading to severe illness, blindness, even death. Aspiration of material into leading to severe illness, blindness, even death. Aspiration of material into leading to enterical pneumonitis which can be fatal.   Carcinogenicity of material None of the components present in this material at concentrations equal to 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.   Reproductive effects None.		ne, impaired memory, loss of coordination, insomnia and ed. Swallowing causes inebriation, headache, vomiting, s, even death. Aspiration of material into lungs can cause e fatal. n this material at concentrations equal to or greater than	
Toxicological Data Ingredients	LC50	D-inh, rat	LD50-Oral,rat
ISOPROPYL ALCOHOL	16,00	00 ppm 8 hours rat inhalation	5,000 mg/kg rat oral 12,800 mg/kg rabbit dermal
ISOBUTANE	52 m	g/L 1 hour mouse	No data
BUTYL CELLOSOLVE	450 p	450 ppm 4 hours rat 470 mg/kg oral rat 400 mg/kg dermal rabbit	
AMMONIA	48.4	mg/L 1 hour rat	350 mg/kg oral rat
	Sectio	on 12: Ecological informatio	on

Environmental
Biodegradability

Do not allow to enter waters, waste water or soil. No data.

#### **PRODUCT: PF 513 GLASS CLEANER**

#### Section 13: Disposal considerations

```
Waste disposal.....
```

This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

#### Section 14: Transport information

TDG Classification (Road)	UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity
	exemption when shipped in containers less than 1 Litre.
DOT Classification (Road)	UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
IATA Classification (Air)	UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity.
IMDG Classification (Marine)	UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
Marine Pollutant	Potential marine pollutant.
	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July
	2, 2014) - we certify that classification of this product is correct.

### Section 15: Regulatory information

WHMIS classification CEPA status OSHA SARA Title III	
Section 302 - extremely hazardoussubstances	Ammonia.
Section 311/312 - hazard categories Section 313 EPA hazardous air pollutants (HAPS) 40CFR63	Isopropyl alcohol. Ammonia.
TSCA inventory status California Proposition 65	

## **Section 16: Other information**

Hazard rate	
NFPA rating	Health: 2 Fire: 4 Reactivity: 0.
HMIS	H: 2 F: 4 R: 0.
Prepared by:	REGULATORY AFFAIRS.
Preparation Date:	November 21, 2014.
Disclaimer:	DISCLAIMER: All information appearing herein is based upon data obtained from
	experience and recognized technical sources. To the best of our knowledge, it is believed
	to be correct as of the date of issue but we make no representations as to its accuracy or
	sufficiency and do not suggest or guarantee that any hazards listed herein are the only
	ones which exist. The hazard information contained herein is offered solely for the
	consideration of the user, subject to his own investigation and verification of compliance
	with applicable regulations, including the safe use of the product under every foreseeable
	condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Disclaimer:	Regulatory Affairs
Last Revision Date	June 2015