

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 29-Jul-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: XTRACTION II

Product Number: 3096

Recommended Use: Carpet cleaner

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 1
Serious Eye Damage/Eye Irritation: Category 1

GHS Label Elements

Signal Word: Danger

Symbols:

Hazard Statements: Causes severe skin burns and serious eye damage.

Precautionary Statements:

Prevention: Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Response: IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

-Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

-Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

-Ingestion:
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

3096 - XTRACTION II Revision Date: 29-Jul-2015

Other Information: • May be harmful if swallowed.

• Inhalation of vapors or mist may cause respiratory irritation.

· Keep out of reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	60-100
alcohol ethoxylate	68439-46-3	1-5
sodium carbonate	497-19-8	1-5
2-butoxyethanol	111-76-2	1-5
tetrasodium ethylenediaminetetraacetate	64-02-8	1-5
sodium alkylnaphthalenesulfonate	111163-74-7	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Take off immediately all contaminated clothing and shoes. Rinse with water or shower for

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash

contaminated clothing before reuse. Discard or destroy contaminated shoes.

-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Ingestion: Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR

PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion, Use extinguishing agent suitable for type of

surrounding fire

Specific Hazards Arising from the

Chemical:

Dried product is capable of burning. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters:

-Skin Contact:

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Methods for Clean-Up: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Keep from freezing.

3096 - XTRACTION II Revision Date: 29-Jul-2015

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Skin and Body Protection:

Wear rubber or other chemical-resistant gloves.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid	
Color:	Light green	
Odor:	Floral fragrance	
pH:	11.2-11.8	
Melting Point / Freezing Point:	No information available.	
Boiling Point / Boiling Range:	100 °C / 212 °F	
Flash Point:	> 100 °C / > 212 °F ASTM D56	
Evaporation Rate:	< 1 (Butyl acetate = 1)	
Flammability (solid, gas)	No information available.	
Upper Flammability Limit:	No information available.	
Lower Flammability Limit:	No information available.	
Vapor Pressure:	No information available.	
Vapor Density:	No information available.	
Specific Gravity:	1.048	
Solubility(ies):	Soluble in water	
Partition Coefficient:	No information available.	
Autoignition Temperature:	No information available.	
Decomposition Temperature:	No information available.	
Viscosity:	No information available.	

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight. Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

Products:

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

3096 - XTRACTION II Revision Date: 29-Jul-2015

Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

-Eye Contact: permanent damage.

Pain, redness, blistering and possible chemical burn. -Skin Contact:

-Inhalation: Nasal discomfort and coughing. Pain, nausea, vomiting and diarrhea. -Ingestion:

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Chronic Toxicity: May cause adverse effects on the bone marrow and blood-forming system. May cause

adverse liver effects.

Target Organ Effects: Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory

System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):

ATEmix (dermal):

9234 mg/kg 30068 mg/kg ATEmix (inhalation-dust/mist): 30 mg/l ATEmix (inhalation-vapor): 108.5 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg(Rat)	Not Available	Not Available
alcohol ethoxylate 68439-46-3	= 1378 mg/kg(Rat)	> 2 g/kg(Rabbit)	Not Available
sodium carbonate 497-19-8	= 4090 mg/kg (Rat)	Not Available	Not Available
2-butoxyethanol 111-76-2	= 470 mg/kg(Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
tetrasodium ethylenediaminetetraacetate 64-02-8	= 10 g/kg(Rat)	Not Available	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
sodium carbonate 497-19-8	242: 120 h Nitzschia mg/L EC50	300: 96 h Lepomis macrochirus mg/L LC50 static 310 - 1220: 96 h Pimephales promelas mg/L LC50 static	Not Available	265: 48 h Daphnia magna mg/L EC50
2-butoxyethanol 111-76-2	Not Available	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	Not Available	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
tetrasodium ethylenediaminetetraacetate 64-02-8	1.01: 72 h Desmodesmus subspicatus mg/L EC50	41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static	Not Available	610: 24 h Daphnia magna mg/L EC50

Persistence and Degradability: No information available. No information available. **Bioaccumulation:**

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Do not reuse container.

3096 - XTRACTION II Revision Date: 29-Jul-2015

14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide)

Hazard Class: 8
Packing Group: |||

Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size,

and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains sodium hydroxide)

Hazard Class: 8
Packing Group: |||

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230

SARA 311/312 Hazard Categories

Acute Health Hazard:YesChronic Health Hazard:YesFire Hazard:NoSudden release of pressure hazard:NoReactive Hazard:No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 3 Flammability: 0 Instability: 0 Special: N/A

HMIS Health Hazards: 3* Flammability: 0 Physical Hazards: 0

Revision Date: 29-Jul-2015 **Reasons for Revision:** Section 14 and 15

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet