

MATERIAL SAFETY DATA SHEET

520968 Johnson Tiling Service

PRODUCT NAME: LATEX PASTE PRODUCTS
PRODUCT CODE: CBTSG50

HMIS CODES: H F R P

1 1 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Custom Building Products, Inc.
ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201
EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846
DATE REVISED : 2-23-00 NAME OF PREPARER : STEVE TAYLOR
REASON REVISED: AREA CODE OF EMERGENCY/INFORMATION PHONE NO. WAS CHANGED.

THE FOLLOWING LIST OF PRODUCTS IS APPLICABLE TO THE MSDS ATTACHED

PATCH N' PAINT
FLEXALL FLEXIBLE ALL-PURPOSE FILLER
EXTERIOR PATCH N' PAINT
PRE-MIXED STUCCO PATCH
CUSTOM PATCH SMOOTH
CUSTOM PATCH TEXTURED
PRE-MIXED CONCRETE PATCH
SEMCO ANTI-FRACTURE MEMBRANE
RELIABOND CERAMIC TILE MASTIC
RELIABOND FAST SETTING CERAMIC TILE MASTIC
RELIABOND EXTENDED SETTING CERAMIC TILE MASTIC
ACRYL-PRO CERAMIC TILE MASTIC
ACRYL 3000 CERAMIC TILE MASTIC
ACRYL 4000 CERAMIC TILE MASTIC
CUSTOM 2000 CERAMIC TILE MASTIC
PRE-MIXED TILE GROUT/WHITE
CUSTOM BOND
INTERIOR SPACKLING PASTE
EXTERIOR SPACKLING PASTE
WALLBOARD JOINT COMPOUND
SQUEEZE N' FILL
WATERPROOFING AND ANTI-FRACTURE MEMBRANE

SECTION II - INGREDIENTS/SARA III INFORMATION

COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE		Wt. %
		OSHA PEL	ACGIH TLV	mm Hg @	TEMP	
*ETHYLENE GLYCOL	107-21-1		50 PPM	0.1	68F	
CALCIUM CARBONATE/	1317-65-3		10 mg.	N/A		
ALIPHATIC HYDROCARBONS	647-4289-8	500		15	68F	
ACRYLIC COPOLYMERS	N/A					

* Chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 212F
 VAPOR DENSITY: HEAVIER THAN AIR
 SOLUBILITY IN WATER: SOLUBLE UNTIL DRIED
 APPEARANCE AND ODOR: WHITE, CREAMY PASTE-MILD ACRYLIC ODOR

SPECIFIC GRAVITY (H2O=1): 1.6
 EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NONE
 FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
 CLOSED CONTAINERS MAY RUPTURE IF EXPOSED TO EXTREME TEMPERATURES.
 WEAR SELF-CONTAINED BREATHING APPARATUS FULL PROTECTIVE GEAR.

UNUSUAL FIRE AND EXPLOSION HAZARDS
 MATERIAL CAN SPLATTER ABOVE 100C/212F. ACRYLIC POLYMER FILM CAN BURN AND CONTAINERS MAY RUPTURE IF EXPOSED TO EXTREME TEMPERATURES.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID
NONE KNOWN

INCOMPATIBILITY (MATERIALS TO AVOID)
AVOID CONTACT WITH STRONG OXIDIZING MATERIALS. ETHYLENE GLYCOL WILL REACT
VIOLENTLY WITH CHLOROSULFONIC ACID, OLEUM, H₂SO₄.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR
CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
INHALATION: VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA, AND IRRITATION OF THE
NOSE THROAT, AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE SKIN CONTACT
IRRITATING TO SKIN UPON REPEATED OR PROLONGED CONTACT.

EYE CONTACT: SLIGHT (TEMPORARY) EYE IRRITATION. CORNEAL INJURY IS UNLIKELY.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
REPEATED SKIN EXPOSURE TO LARGE QUANTITIES MAY RESULT IN ABSORPTION OF HARMFUL
AMOUNTS. THE DERMAL LD₅₀ HAS NOT BEEN DETERMINED.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
THE ORAL LD₅₀ OF ETHYLENE GLYCOL FOR RATS IS IN THE 6000-13000 MG/KG RANGE.
AMOUNTS INGESTED INCIDENTAL TO INDUSTRIAL HANDLING NOT LIKELY TO CAUSE INJURY;
HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY, EVEN DEATH.

HEALTH HAZARDS (ACUTE AND CHRONIC)
ACUTE: PRE-EXISTING SKIN, EYE, AND RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY
EXPOSURE TO ETHYLENE GLYCOL.
CHRONIC: EXCESSIVE EXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM, KIDNEY, BLOOD,
AND POSSIBLE LIVER EFFECTS.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? YES
NOT LISTED AS A CARCINOGEN.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: IMMEDIATELY FLUSH WITH WATER FOR 15 MIN. SEE PHYSICIAN IF
IRRITATION RESULTS.
SKIN CONTACT: WASH WITH AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION RESULTS.
INHALED: IF AFFECTED, REMOVE TO FRESH AIR.

INGESTION: IMMEDIATELY INDUCE VOMITING BY GIVING TWO GLASSES OF WATER AND
STICKING FINGER DOWN THROAT. CALL A PHYSICIAN.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: AVOID ENTRY INTO SEWERS OR NATURAL WATER WAYS. SMALL SPILLS: SOAK UP WITH ABSORBANT MATERIAL. LARGE SPILLS: DIKE AND PUMP INTO SUITABLE CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE IN COOL, DRY AREA OUT OF SUNLIGHT. STORE AWAY FROM HEAT OR ANY HEAT SOURCES. PROTECT FROM FREEZING.

OTHER PRECAUTIONS - NONE

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION IF EXPOSURE MAY EXCEED TLV RANGE, USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

VENTILATION GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP VAPOR CONCENTRATIONS WITHIN SPECIFIED TLV RANGES.

PROTECTIVE GLOVES THE USE OF PLASTIC OR RUBBER GLOVES IS ADVISED TO PREVENT SKIN IRRITATION OF SENSITIVE INDIVIDUALS.

EYE PROTECTION SAFETY GLASSES ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: ADEQUATE CLOTHING SHOULD BE WORN TO PREVENT SKIN CONTACT.

WORK/PRACTICES HYGEINE AND GOOD HOUSEKEEPING PRACTICES SHOULD BE OBSERVED.

SECTION IX - DISCLAIMER

DISCLAIMER

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.