



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** QD® Contact Cleaner

**Other means of identification**

**Product code** 03130

**Recommended use** Electronic cleaner

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs (central nervous system, eyes, skin, upper respiratory tract) through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe gas. Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

### Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical attention. Collect spillage.

### Storage

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

### Disposal

Dispose of contents/container in accordance with local/regional/national regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

---

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), hydrotreated light		64742-49-0	60 - 70
1,1-Difluoroethane	HFC-152a	75-37-6	20 - 30
n-Hexane		110-54-3	3 - 5
2,2,4-Trimethylpentane		540-84-1	1 - 3
Isopropyl alcohol		67-63-0	1 - 3
2,2-Dimethylbutane		75-83-2	< 0.2
2-Methylpentane		107-83-5	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

---

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin contact

Rinse skin with water/shower. Get medical attention if irritation develops and persists.

### Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

### Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Prolonged exposure may cause chronic effects.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

---

## 5. Fire-fighting measures

### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

### Unsuitable extinguishing media

None known.

<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist or vapor. Do not breathe gas. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.
<b>Conditions for safe storage, including any incompatibilities</b>	Level 3 Aerosol.  Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2,2,4-Trimethylpentane (CAS 540-84-1)	PEL	2350 mg/m3
Isopropyl alcohol (CAS 67-63-0)	PEL	500 ppm 980 mg/m3
n-Hexane (CAS 110-54-3)	PEL	400 ppm 1800 mg/m3 500 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
2,2-Dimethylbutane (CAS 75-83-2)	STEL	1000 ppm
2-Methylpentane (CAS 107-83-5)	TWA	500 ppm
	STEL	1000 ppm
Isopropyl alcohol (CAS 67-63-0)	TWA	500 ppm
	STEL	400 ppm
n-Hexane (CAS 110-54-3)	TWA	200 ppm
	TWA	50 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2,2,4-Trimethylpentane (CAS 540-84-1)	Ceiling	1800 mg/m3
	TWA	385 ppm 350 mg/m3 75 ppm
2,2-Dimethylbutane (CAS 75-83-2)	Ceiling	1800 mg/m3
	TWA	510 ppm 350 mg/m3 100 ppm
2-Methylpentane (CAS 107-83-5)	Ceiling	1800 mg/m3
	TWA	510 ppm 350 mg/m3 100 ppm
Isopropyl alcohol (CAS 67-63-0)	STEL	1225 mg/m3
	TWA	500 ppm 980 mg/m3 400 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3 50 ppm

#### US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3 1000 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton®.

**Other**

Wear suitable protective clothing. Use of an impervious apron is recommended.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

---

**9. Physical and chemical properties**


---

**Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Clear. Colorless.

**Odor**

Alcoholic.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

-127.3 °F (-88.5 °C) estimated

**Initial boiling point and boiling range**

123 °F (50.6 °C) estimated

**Flash point**

< 0 °F (< -17.8 °C) Tag Closed Cup

**Evaporation rate**

Very fast.

**Flammability (solid, gas)**

Not available.

**Upper/lower flammability or explosive limits****Flammability limit - lower (%)**

0.9 % estimated

**Flammability limit - upper (%)**

12 % estimated

**Vapor pressure**

2141.3 hPa estimated

**Vapor density**

> 1 (air = 1)

**Relative density**

0.72 estimated

**Solubility (water)**

Negligible.

<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	489.2 °F (254 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity (kinematic)</b>	Not available.
<b>Percent volatile</b>	100 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
QD® Contact Cleaner		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	2807.0864 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	29004.0918 ppm, 4 hours estimated 29.3555 mg/l, 4 hours estimated
<i>Oral</i>		
LD50	Rat	21091.707 mg/kg estimated

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>Reproductive toxicity</b>	Suspected of damaging fertility.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.

<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure: Central nervous system. Eyes. Skin. Upper respiratory tract.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Product	Species	Test Results
QD® Contact Cleaner		
<b>Aquatic</b>		
Fish	LC50	Fish 1703.5929 mg/l, 96 hours estimated
Components	Species	Test Results
Isopropyl alcohol (CAS 67-63-0)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 7550 - 13299 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 3200 mg/l, 96 hours
n-Hexane (CAS 110-54-3)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

1,1-Difluoroethane	0.75
2,2,4-Trimethylpentane	5.18
2,2-Dimethylbutane	3.82
2-Methylpentane	3.74
Isopropyl alcohol	0.05
n-Hexane	3.9

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal of waste from residues / unused products** If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

**DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.



**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Special provisions** N82  
**Packaging exceptions** 306  
**Packaging non bulk** None  
**Packaging bulk** None

#### IATA

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable, Limited Quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards** Yes  
**ERG Code** 10L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**  
**Passenger and cargo aircraft** Allowed.  
**Cargo aircraft only** Allowed.

#### IMDG

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, LIMITED QUANTITY, MARINE POLLUTANT  
**Transport hazard class(es)**  
**Class** 2  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** Yes  
**EmS** F-D, S-U  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**General information** IMDG Regulated Marine Pollutant.

---

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### SARA 304 Emergency release notification

Not regulated.

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

n-Hexane (CAS 110-54-3)

### CERCLA Hazardous Substance List (40 CFR 302.4)

2,2,4-Trimethylpentane (CAS 540-84-1)

n-Hexane (CAS 110-54-3)

### CERCLA Hazardous Substances: Reportable quantity

2,2,4-Trimethylpentane (CAS 540-84-1) 1000 LBS

n-Hexane (CAS 110-54-3) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2,2,4-Trimethylpentane (CAS 540-84-1)

n-Hexane (CAS 110-54-3)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)



**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 311/312 Hazard categories**  
Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**US state regulations**

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. New Jersey Worker and Community Right-to-Know Act**

2,2,4-Trimethylpentane (CAS 540-84-1)  
2,2-Dimethylbutane (CAS 75-83-2)  
2-Methylpentane (CAS 107-83-5)  
1,1-Difluoroethane (CAS 75-37-6)  
Isopropyl alcohol (CAS 67-63-0)  
n-Hexane (CAS 110-54-3)

**US. Massachusetts RTK - Substance List**

1,1-Difluoroethane (CAS 75-37-6)  
2,2,4-Trimethylpentane (CAS 540-84-1)  
Isopropyl alcohol (CAS 67-63-0)  
n-Hexane (CAS 110-54-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Isopropyl alcohol (CAS 67-63-0)  
2,2,4-Trimethylpentane (CAS 540-84-1)  
2,2-Dimethylbutane (CAS 75-83-2)  
2-Methylpentane (CAS 107-83-5)  
n-Hexane (CAS 110-54-3)

**US. Rhode Island RTK**

1,1-Difluoroethane (CAS 75-37-6)  
2,2,4-Trimethylpentane (CAS 540-84-1)  
n-Hexane (CAS 110-54-3)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**Volatile organic compounds (VOC) regulations**

**EPA**

**VOC content (40 CFR 51.100(s))** 74.3 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

**State**

**Consumer products** This product is regulated as an Electronic Cleaner. This product is compliant for use in all 50 states.

**VOC content (CA)** 74.3 %

**VOC content (OTC)** 74.3 %

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	09-29-2014
<b>Prepared by</b>	Allison Cho
<b>Version #</b>	01
<b>Further information</b>	CRC # 957
<b>HMIS® ratings</b>	Health: 1* Flammability: 4 Physical hazard: 0 Personal protection: B
<b>NFPA ratings</b>	Health: 1 Flammability: 4 Instability: 0

### NFPA ratings



### Disclaimer

CRC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.