

MATERIAL SAFETY DATA SHEET

MANUFACTURED BY: Fourstar Chemical
3137 26th Street
Los Angeles, CA. 90023
(323) 266-7111

DISTRIBUTED BY: JASCO CHEMICAL CORP
**#0206 PAINT AND GRAFFITTI
REMOVER,** (6 CAN CASE)

PRODUCT ID NO.: 32760

24 - HOUR
EMERGENCY
TELEPHONE
(800) 255-3924

24 - HOUR
EMERGENCY
TELEPHONE
(800) 424-9300

PAGE: 1

EFFECTIVE DATE: 08/06/02
PRODUCT ID NO.: 32760

DATE PREPARED: 5/12/03

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200
(The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT DESCRIPTION: JASCO CHEMICAL CORP. #206 PAINT AND GRAFFITTI
REMOVER, (6 CAN CASE)

D.O.T. PROPER SHIPPING NAME: ORM-D

CONSUMER COMMODITY

NFPA CODES: HEALTH - 3 FLAMMABILITY - 3 CORROSIVE - 1 REACTIVITY - 0

SECTION II - COMPONENTS

METHYL ALCOHOL	* PEL:	200 PPM
CAS #: 67-56-1	TLV:	200 PPM
DICHLOROMETHANE	* PEL:	TWA 25 PPM
CAS #: 75-09-2	TLV:	ACGIH 50 PPM
AROMATIC HYDROCARBON	* PEL:	TWA OF 100 ppm (375 mg/m3)
CAS #: 108-88-3	TLV:	TWA OF 50 ppm (147 mg/m3)
AMMONIUM HYDROXIDE	PEL:	50 PPM
CAS #: 7664-41-7	TLV:	35 PPM
HYDROCARBON PROPELLANT	PEL:	800 PPM
CAS #: 68476-86-8	TLV:	800 PPM

"" If Present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section.

SECTION III - PHYSICAL DATA

BOILING POINT FOR PRODUCT: N/D
VAPOR PRESSURE FOR PRODUCT: 31PSIG@75F
VAPOR DENSITY FOR PRODUCT: N/D
SPECIFIC GRAVITY: 1.154
V.O.C. (GRAMS PER LITER): 129 LIQUID ONLY
WATER SOLUBILITY: NEGLIGIBLE
APPEARANCE: AMBER SOLVENT LIQUID

MATERIAL SAFETY DATA SHEET

PAINT AND GRAFFITTI REMOVER (AEROSOL)

PAGE 2

===== SECTION IV - FIRE AND EXPLOSION HAZARD =====

FLASH POINT (TOC): LEVEL 2 AEROSOL
EXPLOSIVE LIMIT (PRODUCT): LOWER - N/D UPPER - N/D
SEC04.22
AUTOIGNITION TEMPERATURE: Not available

EXTINGUISHING MEDIA: Fires involving this product are unlikely, but should on occur, it may be controlled by carbon dioxide, dry chemicals or water spray.

SPECIAL FIREFIGHTING PROCEDURES: Pressure-demand, self-contained breathing apparatus should be provided for fire fighters in building or confined areas where product is stored. Storage containers exposed to fire should be kept cool with water spray, in order to prevent pressure buildup.

UNUSUAL FIRE AND EXPLOSION HAZARD: At high temperatures, this product decomposes to give off hydrochloric acid gas plus other toxic and irritating vapors such as phosgene. If storage containers are exposed to excessive heat, over-pressurization of containers can result.

===== SECTION V - HEALTH HAZARD DATA =====

SEC05.22
ROUTES OR EXPOSURE:

INHALATION: Excessive inhalation may produce symptoms of central nervous system depression, ranging from light-headedness, nausea and vomiting, to unconsciousness and death.

SKIN: Mildly irritating to skin. Skin contact may produce a burning sensation—prolonged or repeated contact may cause skin to become reddened, rough, and dry due to the removal of natural oils and may result in dermatitis.

May be absorbed through the skin, although not expected to produce toxicity through this route.

EYE CONTACT: An irritant of the eyes, causing pain, lacrimation and general inflammation.

INGESTION: May cause irritation of the gastrointestinal tract with vomiting. If vomiting results in aspiration, chemical pneumonia may follow. Absorption through the gastrointestinal tract may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness.

EFFECTS OF OVEREXPOSURE:

ACUTE: Excessive inhalation or ingestion may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness and death. Overexposure may result in liver and kidney damage. Exposure of the eyes and skin may produce irritation. Animals exposed to high levels have shown cardiac sensitization.

CHRONIC: Can cause headache, mental confusion, depression, fatigue, loss of sense of balance, and visual disturbances. Prolonged or repeated skin contact may cause dermatitis.

HYGIENE: Avoid contact with skin and avoid breathing vapors. Do not eat, drink or smoke in work area. Wash hands prior to eating, drinking or using restroom.

MATERIAL SAFETY DATA SHEET

PAINT AND GRAFFITTI REMOVER (AEROSOL)

PAGE 3

=====**SECTION V - HEALTH HAZARD DATA (CONTINUED)**=====

FIRST AID:

EYES: Irrigate with flowing water immediately and continuously for 15 minutes. Consult medical personnel.

SKIN: Wash off in flowing water or shower.

INGESTION: Do not induce vomiting. Call physician and/or transport to emergency facility immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call physician and/or transport to a medical facility.

NOTE TO PHYSICIAN: Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighted against toxicity when considering emptying the stomach. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs unless absolutely necessary.

(PROPOSITION 65) : SEC05

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL (S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

=====**SECTION VI - REACTIVITY DATA**=====

SEC06.20

STABILITY: Stable

CONDITIONS TO AVOID: Not applicable

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

=====**SECTION VII - SPILL OR LEAK PROCEDURES**=====

SEC07.45

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD:

Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved facilities.

MATERIAL SAFETY DATA SHEET

PAINT AND GRAFFITTI REMOVER (AEROSOL)

PAGE 4

===== **SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED** =====

SEC08.22

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyflourinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing.

Standard work shoes; discard if shoes cannot be decontaminated.

Store contaminated clothing in well-ventilated cabinets or closed containers.

Wash contaminated clothing and dry before reuse.

MONITORING EXPOSURE:

BIOLOGICAL: No applicable procedures can be recommended.

PERSONAL/AREA: Use NIOSH ANALYTICAL METHOD NUMBER 1003 for halogenated hydrocarbons.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

===== **SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS** =====

SEC09.45

HANDLING STORAGE AND DECONTAMINATION PROCEDURES: When utilizing pressurized containers follow standard safety practices for handling aerosols.

GENERAL COMMENTS: Do not store at temperatures above 120 degree F. Odor is not an adequate warning of potentially hazardous concentrations in air. Releases of these gases may cause a flammable atmosphere with explosion potential.

PRECAUTINARY STATEMENTS: Please read and follow the directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

===== **ADDITIONAL COMMENTS** =====

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.