Date Printed: 11-15-1989 Page

MATERIAL SAFETY DATA SHEET MSDS for 4-1175 ISOPROPYL ALCOHOL

-Section I - Product Identification Manufacturer's Name Emergency Phone Number (24 Hours) A.B.DICK COMPANY (312) 763-1900 Date Prepared Street Address 5700 WEST TOUHY AVENUE MAY/15/1989 City,State,Zip Code CHICAGO ILLINOIS 60648 Prepared By KENNETH W. PINTER Product Use: OFFSET PRINTING. Chemical Name, Trade Name, Synonyms: ISOPROPANOL, 2-PROPANOL. HMIS RATING 2 - Health 3 - Flammability 0 - Reactivity B - Personal Protection -Section II - Hazardous Ingredients Hazardous Exposure Limits CAS NO. ; % WT.; OSHA PEL ACGIH TLV OTHER Components ISOPROPYL ALCOHOL 67-63-0 100 | 400 PPM. 400 PPM. 3 -Section III - Physical Data Boiling POINT(F): 180 pH: N.A. Vapor Pressure(mm Hg): 33 | Freezing Point(F): N.A. \_\_\_\_\_\_

Specific Gravity (H2O=1): 0.789 Color And Odor: COLORLESS / ALCOHOL

Date Printed: 11-15-1989 MATERIAL SAFETY DATA SHEET MSDS for 4-1175 ISOPROPYL ALCOHOL -Section III - Physical Data (continued) dor Threshold: 7.5 PPM Physical State: LIQUID. Evaporation Rate (Butyl Acetate = 1): 1.4 Solubility in Water: COMPLETE. -Section IV - Fire and Explosion Hazard Data FLASH POINT (METHOD USED): 53 (F) T.C.C. |Flammable Limits: LEL: 2.0% UEL: 12.0% Auto-ignition Temperature: N.D. Extinguishing Media: WATER FOG / ALCOHOL FOAM / CO2 / DRY CHEMICAL. Special Fire Fighting Procedures: USE APPROVED RESPIRATORS. WATER MAY BE FFECTIVE IN ADVANCED FIRES, BUT CAN BE USED TO KEEP FIRE EXPOSED CONTAINERS FIREFIGHTERS COOL. WATER WILL DILUTE SMALL SPILLS TO A NON-FLAMMABLE MIXTURE. Unusual Fire And Explosion Hazards: LOW FLASH POINT. 5 -Section V - Reactivity Data Stability Unstable : Stable : X Conditions to Avoid: OPEN FLAMES AND ELECTRICAL SPARKS. KEEP CONTAINER CLOSED WHEN NOT IN USE, ! DO NOT SMOKE WHILE USING. Incompatibility (Materials to Avoid): STRONG OXIDIZING MATERIAL. Hazardous Decomposition Products: POSSIBLY CARBON MONOXIDEAND AND UNIDENTIFIED ORGANIC COMPOUNDS. Hazardous | May Occur: Conditions to Avoid: HEAT, SPARKS AND Polymerization | Will Not Occur: X | OPEN FLAME.

6 -Section VI - Health Hazard Data (Acute and Chronic) 

Primary Route(s) of Entry: DERMAL, INHALATION.

Oral Ingestion: MAY CAUSE MARKED AND PERSISTENT NAUSEA, VOMITING AND ABDOMINAL PAIN. IF VOMITING OCCUR FOLLOWING INGESTION, ASPIRATION OF VOMITUS INTO THE LUNGS CAN CAUSE BROCHOPNEUMONIA OR PULMONARY EDEMA. 

Eye Contact: LIQUID OR VAPOR CONTACT CAN CAUSE IRRITATION.

Skin Contact: PROLONGED AND REPEATED CONTACT CAN CAUSE DRYNESS AND IRRITATION.

Inhalation: HIGH CONCENTRATIONS OF VAPORS CAN IRRITATE RESPIRATORY TRACT AND MAY RESULT IN CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION.

Effects of Overexposure: HIGH CONCENTRATION OF VAPOR CAN HEADACHES, DIZZINESS NAUSEA, INCOORDINATION, DROWSINESS AND LOSS OF CONSCIONSNESS.

Medical Conditions Generally! PREEXISTING SKIN, EYE AND RESPIRATORY DISORDERS. Aggravated by Exposure

Carcinogenicity: NOT KNOWN TO BE CARCINOGENIC.PRESENT.

Mutagenicity: NOT KNOWN TO BE MUTAGENIC.

\_\_\_\_\_\_ Teratogenicity: NOT KNOWN TO BE TERATOGENIC. 

Reproductive Toxicity: NOT KNOWN TO HAVE REPRODUCTIVE TOXICITY.

FIRST AID PROCEDURES

Ingestion: GIVE NO MORE THAN 2 GLASSES OF WATER AND INDUCE VOMITING BY GIVING 2 TABLE SPOONS SYRUP OF IPECAC. GET MEDICAL ATTENTION IMMEDIATELY.

Eye: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

Skin: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

Inhalation: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

Precautions to be taken in Handling and Storing: WARNING! FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME. KEEP CONTAINER CLOSED. AVOID REPEATED EYE AND SKIN CONTACT. AVOID INHALATION OF HIGH CONCENTRATIONS OF VAPOR. USE WITH "ENTILATION TO MAINTAIN VAPOR CONCENTRATIONS BELOW THE TLV OF 400 PPM.

· · · · · · · · · · · · · · · · · · ·
Date Printed: 06-30-1989 Page 5 MATERIAL SAFETY DATA SHEET MSDS for 4-1175 ISOPROPYL ALCOHOL
10 -Section X - Special Precautions (continued)
Other Precautions: KEEP OUT OF REACH OF CHILDREN.
11 -Section XI - Transportation Information
Hazard Class: FLAMMABLE LIQUID. DOT Proper Shipping Name: ISOPROPANOL, FLAMMABLE LIQUID. UN 1219
12 -Section XII - Regulatory Information
CERCLA/SUPERFUND,40 CFR 117,302: THIS PRODUCT DOES NOT CONTAIN ANY REPORTABLE QUANTITY (RQ) SUBSTANCE.
SARA(TITLE III) - Sections 302, 311, 312, and 313:
Section 302 Extremely Hazardous Substances (40 CFR 355): THIS PRODUCT DOES NO CONTAIN ANY INGREDIENTS LISTED AS AN EXTREMELY HAZARDOUS SUBSTANCE.
Section 311 and 312 MSDS Submission and Inventory Reporting (40 CFR 370): THIS PRODUCT CONTAINS ISOPROPYL ALCOHOL WHICH REQUIRES REPORTING UNDER 311 AND 312 IF STORED IN LARGE ENOUGH QUANTITIES.  Section 313 Toxic Chemical Release Reporting (40 CFR 372): THIS PRODUCT DOES NOT CONTAIN ANY INGREDIENTS THAT ARE ON THE LIST OF TOXIC CHEMICALS.
TOXIC SUBSTANCES CONTROL ACT (TSCA): This product complies with rules and regulations of TSCA.
California Proposition 65: THIS PRODUCT DOES NOT CONTAIN ANY MATERIAL, THAT ARE CURRENTLY LISTED BY THE STATE OF CALIFORNIA UNDER PROPOSITION 65.

13 -Section XIII - Addition Information

NONE

Date Printed: 06-30-1989 Page 6
MATERIAL SAFETY DATA SHEET
MSDS for 4-1175 ISOPROPYL ALCOHOL

13 -Section XIII - Addition Information (continued)

The information herein given in good faith but no warranty, express or implied, is made.